



Jeger Onyks is a ready-to-use decorative coating, which allows you to obtain a shimmering surface with characteristic pits. The product is designed for interior and outdoor use.

You can do it yourself in one day!

It's just 2 steps

Only 2 tools



1 Apply Jeger Primer Onyks



Apply **Jeger Primer Onyks** on a clean, dry, dust-free and degreased wall with a paint roller. Leave it to dry for 2-4 hours. Remember to use adequate color of the primer to the **Jeger Onyks** color later applied on the wall.

2 Apply Jeger Onyks with a Venetian trowel



Mix the product well before use. Do NOT dilute, the product is ready to use. Do NOT mix with other products. Apply a grain-boundary thickness layer with a venetian trowel and then gently smooth it out. If you want to obtain pits effect, place a venetian trowel on a freshly applied coating and pull on the trowel fast towards yourself. At the stage of preliminary drying time, gently smooth the entire surface. Leave it to dry for 12 hours.

Tip: If you want to achieve the effect of sparkling crystals, add **Jeger Glitter Gel** to **Jeger Onyks** before applying the product (about 100g of glitter for every 7kg of the product, mix it well).

Remember: If you need to use more than one package of product, mix them well before use. This way you will get a usolid color. Before applying the products, including process of varnishing, check the effect on a small area.

7kg > ±6m²
14kg > ±12m²

jeger.com



The efficiency of the product and the number of paint layers depend on the structure and absorpency of the painted surface, its thickness, application methods and the contractor's experience.

Global Point, ul. Rozwoju 3, Biskupice Podgórne, 55-040 Kobierzyce

MADE IN POLAND