

You can do it yourself in one day!

It's just 3 steps

Only 3 tools: a roller

+ microfiber cloth

a venetian trowel

Apply the primer with a roller





Apply the **Jeger Primer for decorative paints** with a microfiber roller to a clean, degreased, dust-free and dry surface. Leave it to dry for about 4 hours. For light colors, it is recommended to apply two coats of primer.

Apply Jeger Stiuk with a venetian trowel









Thoroughly mix **Jeger Stiuk**. Do NOT dilute with water. Do NOT mix with other products. Apply an even, thin layer of the product using a Venetian trowel. Apply the product in small sections, spreading it irregularly in all directions. Leave it to dry for 2 hours. Before applying the second layer, smooth the surface with the trowel. Apply the second layer the same way as the first one. When the product starts to dry, polish the entire surface with the trowel following an irregular pattern of random motions in all directions. Apply the product at temperatures ranging from +8°C to +25°C, with a maximum relative humidity of 82%, avoiding drafts. After finishing the work, clean the tools with warm water.

After about 2 hours, polish the wall using a microfiber cloth.

Remember: If you need to use more than one container of the product, mix the contents of all containers together before applying. This ensures a uniform shade. Before proceeding with the entire application, test the product on a small surface. The product is intended for indoor use.

coverage per container (2L)

jeger.com

